



| Model      | X1        | X2         | H    |
|------------|-----------|------------|------|
| <b>50</b>  | 485-495   | maks. 1500 | 2000 |
| <b>55</b>  | 535-545   | maks. 1500 | 2000 |
| <b>60</b>  | 585-595   | maks. 1500 | 2000 |
| <b>65</b>  | 635-645   | maks. 1500 | 2000 |
| <b>70</b>  | 685-695   | maks. 1500 | 2000 |
| <b>75</b>  | 735-745   | maks. 1500 | 2000 |
| <b>80</b>  | 785-795   | maks. 1500 | 2000 |
| <b>85</b>  | 835-845   | maks. 1500 | 2000 |
| <b>90</b>  | 885-895   | maks. 1500 | 2000 |
| <b>95</b>  | 935-945   | maks. 1500 | 2000 |
| <b>100</b> | 985-995   | maks. 1500 | 2000 |
| <b>105</b> | 1035-1045 | maks. 1500 | 2000 |
| <b>110</b> | 1085-1095 | maks. 1500 | 2000 |
| <b>115</b> | 1135-1145 | maks. 1500 | 2000 |
| <b>120</b> | 1185-1195 | maks. 1500 | 2000 |
| <b>125</b> | 1235-1245 | maks. 1500 | 2000 |
| <b>130</b> | 1285-1295 | maks. 1500 | 2000 |
| <b>135</b> | 1335-1345 | maks. 1500 | 2000 |
| <b>140</b> | 1385-1395 | maks. 1500 | 2000 |
| <b>145</b> | 1435-1445 | maks. 1500 | 2000 |
| <b>150</b> | 1485-1495 | maks. 1500 | 2000 |
| <b>155</b> | 1535-1545 | maks. 1500 | 2000 |
| <b>160</b> | 1585-1595 | maks. 1500 | 2000 |